

Certificate

Issue Date: February 26, 2013

Ref. Report No. ISL-13HE041CE

Product Name : Nuvo-2000+ Series
Models : Nuvo-2021DV+; Nuvo-2030DV+; Nuvo-2021+; Nuvo-2030+
Responsible Party : Neousys Technology Inc.
Address : 15F., No.868-3, Zhongzheng Rd., Zhonghe Dist., New Taipei City 23586, Taiwan(R.O.C.)

We, **International Standards Laboratory**, hereby certify that:

The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in European Council Directive- EMC Directive 2004/108/EC. The device was passed the test performed according to :



Standards:

EN 61000-6-4:2007+A1:2011 and IEC 61000-6-4:2006+A1:2010 : Generic standards – Emission Standard for industrial environments.

EN 61000-6-2: 2005 and IEC 61000-6-2: 2005: EMC – Generic standards – Immunity for industrial environments.

EN61000-3-2: 2006+A1:2009 +A2:2009 and IEC 61000-3-2: 2005 +A1:2008 +A2:2009: Limits for harmonics current emissions

EN61000-3-3: 2008 and IEC 61000-3-3: 2008: Limits for voltage fluctuations and flicker in low-voltage supply systems.

EN 55022: 2010 and CISPR 22: 2008 (modified)

EN 55024: 2010 and CISPR 24: 2010

EN 61000-4-2: 2009 and IEC 61000-4-2: 2008

EN 61000-4-3: 2006+A1: 2008 +A2: 2010 and

IEC 61000-4-3:2006+A1: 2007+A2: 2010

EN 61000-4-4: 2004 +A1:2010 and IEC 61000-4-4: 2004 +A1:2010

EN 61000-4-5: 2006 and IEC 61000-4-5: 2005

EN 61000-4-6: 2009 and IEC 61000-4-6: 2008

EN 61000-4-8: 2010 and IEC 61000-4-8: 2009

EN 61000-4-11: 2004 and IEC 61000-4-11: 2004

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

International Standards Laboratory

Jim Chu / Director

☒ **Hsi-Chih LAB:**

No. 65, Gu Dai Keng St., Hsichih District,
New Taipei City 22179, Taiwan.

Tel: 886-2-2646-2550; Fax: 886-2-2646-4641



CE MARK TECHNICAL FILE

AS/NZS EMC CONSTRUCTION FILE

of

Product Name

Nuvo-2000+ Series

Models

**Nuvo-2021DV+; Nuvo-2030DV+; Nuvo-2021+;
Nuvo-2030+**

Contains:

1. Declaration of Conformity
2. EN61000-6-4, EN55022/CISPR 22EMI test report
3. EN61000-6-2, EN55024/CISPR 24, EN61000-3-2, and EN61000-3-3 test report
4. Block Diagram and Schematics
5. Users' manual

Declaration of Conformity

Name of Responsible Party: Neousys Technology Inc.

Address of Responsible Party: 15F., No.868-3, Zhongzheng Rd., Zhonghe Dist., New Taipei City 23586, Taiwan(R.O.C.)

Declares that product: Nuvo-2000+ Series

Models: Nuvo-2021DV+; Nuvo-2030DV+; Nuvo-2021+; Nuvo-2030+

Assembled by: Same as above

Address: Same as above

Conforms to the EMC Directive 2004/108/EC as attested by conformity with the following harmonized standards:

EN 61000-6-4:2007+A1:2011 and IEC 61000-6-4:2006+A1:2010 : Generic standards – Emission Standard for industrial environments.

EN 61000-6-2: 2005 and IEC 61000-6-2: 2005: EMC – Generic standards – Immunity for industrial environments.

EN 55022:2010, CISPR 22:2008 (modified) and AS/NZS CISPR 22: 2009: Limits and methods of measurement of Radio Interference characteristics of Information Technology Equipment.

EN 55024:2010 and CISPR 24:2010: Information technology equipment-Immunity characteristics - Limits and methods of measurement.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008 +A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4: 2004 +A1:2010 IEC 61000-4-4: 2004 +A1:2010	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5: 2006 IEC 61000-4-5: 2005	Surge	Pass	B
EN 61000-4-6:2009 IEC 61000-4-6:2008	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11: 2004 IEC 61000-4-11: 2004	Voltage Dips / Short Interruption and Voltage Variation		
	100% in 20ms	Pass	B
	30% in 500ms	Pass	C
	60% in 2000ms	Pass	C
	100% in 5000ms	Pass	C

<to be continued>

Standard	Description	Results
EN 61000-3-2: 2006 +A1:2009 +A2:2009 IEC 61000-3-2: 2005 +A1:2008 +A2:2009	Limits for harmonics current emissions	Pass
EN 61000-3-3: 2008 IEC 61000-3-3: 2008	Limits for voltage fluctuations and flicker in low-voltage supply systems.	Pass

We, Neousys Technology Inc., hereby declare that the equipment bearing the trade name and model number specified above was tested conforming to the applicable Rules under the most accurate measurement standards possible, and that all the necessary steps have been taken and are in force to assure that production units of the same equipment will continue to comply with the requirements.

Neousys Technology Inc.

Date: 2/26/2013

Declaration of Conformity

Name of Responsible Party: Neousys Technology Inc.

Address of Responsible Party: 15F., No.868-3, Zhongzheng Rd., Zhonghe Dist., New Taipei City 23586, Taiwan(R.O.C.)

Declares that product: Nuvo-2000+ Series

Models: Nuvo-2021DV+; Nuvo-2030DV+; Nuvo-2021+; Nuvo-2030+

Assembled by: Same as above

Address: Same as above

Conforms to the C-Tick Mark requirement as attested by conformity with the following standards:

EN 61000-6-4:2007+A1:2011 and IEC 61000-6-4:2006+A1:2010 : Generic standards – Emission Standard for industrial environments.

EN 61000-6-2: 2005 and IEC 61000-6-2: 2005: EMC – Generic standards – Immunity for industrial environments.

EN 55022:2010, CISPR 22:2008 (modified) and AS/NZS CISPR 22: 2009: Limits and methods of measurement of Radio Interference characteristics of Information Technology Equipment.

EN 55024:2010 and CISPR 24:2010: Information technology equipment-Immunity characteristics - Limits and methods of measurement.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008 +A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4: 2004 +A1:2010 IEC 61000-4-4: 2004 +A1:2010	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5: 2006 IEC 61000-4-5: 2005	Surge	Pass	B
EN 61000-4-6:2009 IEC 61000-4-6:2008	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11: 2004 IEC 61000-4-11: 2004	Voltage Dips / Short Interruption and Voltage Variation		
	100% in 20ms	Pass	B
	30% in 500ms	Pass	C
	60% in 2000ms	Pass	C
	100% in 5000ms	Pass	C

<to be continued>

Standard	Description	Results
EN 61000-3-2: 2006 +A1:2009 +A2:2009 IEC 61000-3-2: 2005 +A1:2008 +A2:2009	Limits for harmonics current emissions	Pass
EN 61000-3-3: 2008 IEC 61000-3-3: 2008	Limits for voltage fluctuations and flicker in low-voltage supply systems.	Pass

We, Neousys Technology Inc., hereby declare that the equipment bearing the trade name and model number specified above was tested conforming to the applicable Rules under the most accurate measurement standards possible, and that all the necessary steps have been taken and are in force to assure that production units of the same equipment will continue to comply with the requirements.

Neousys Technology Inc.

Date: 2/26/2013

CE TEST REPORT

of
EN61000-6-4
EN55022 / CISPR 22
Class A
EN61000-6-2
EN55024 / CISPR 24 / IMMUNITY

Product : **Nuvo-2000+ Series**

Models: **Nuvo-2021DV+; Nuvo-2030DV+;**
Nuvo-2021+; Nuvo-2030+

Applicant: **Neousys Technology Inc.**

Address: **15F., No.868-3, Zhongzheng Rd., Zhonghe**
Dist., New Taipei City 23586, Taiwan(R.O.C.)

Test Performed by:

International Standards Laboratory

<Hsi-Chih LAB>

*Site Registration No.

BSMI:SL2-IN-E-0037; SL2-R1/R2-E-0037; TAF: 1178

FCC: TW1067; IC: IC4067A-1; NEMKO: ELA 113A

VCCI: <Conduction01>C-354, T-1749, <OATS01>R-341,

<Chamber01>G-443

*Address:

No. 65, Gu Dai Keng St.

Hsichih District, New Taipei City 22179, Taiwan

*Tel: 886-2-2646-2550; Fax: 886-2-2646-4641

Report No.: **ISL-13HE041CE**

Issue Date : **February 26, 2013**

This report totally contains 56 pages including this cover page and contents page.

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory.



Contents of Report

1.	General.....	1
1.1	Certification of Accuracy of Test Data	1
1.2	Test Standards	2
1.3	Description of EUT	5
1.4	Description of Support Equipment	7
1.5	Software for Controlling Support Unit.....	8
1.6	I/O Cable Condition of EUT and Support Units	9
2.	Power Main Port Conducted Emissions	10
2.1	Test Setup and Procedure	10
2.2	Conduction Test Data: Configuration 1	11
2.3	Test Setup Photo.....	13
3.	Telecommunication Port Conducted Emissions	15
3.1	Test Setup and Procedure	15
3.2	Test Data: LAN--10M: Configuration 1.....	16
3.3	Test Data: LAN--100M: Configuration 1.....	17
3.4	Test Data: LAN--GIGA: Configuration 1	18
3.5	Test Data: LAN--GIGA: Configuration 2	19
3.6	Test Setup Photo.....	20
4.	Radiated Disturbance Emissions	21
4.1	Test Setup and Procedure	21
4.2	Radiation Test Data: Configuration 1.....	23
4.3	Test Setup Photo.....	27
5.	Electrostatic discharge (ESD) immunity	29
5.1	Test Specification	29
5.2	Test Setup	29
5.3	Test Result	29
5.4	Test Point.....	30
5.5	Test Setup Photo.....	31
6.	Radio-Frequency, Electromagnetic Field immunity.....	32
6.1	Test Specification	32
6.2	Test Setup	32
6.3	Test Result	32
6.4	Test Setup Photo.....	33
7.	Electrical Fast transients/burst immunity	34
7.1	Test Specification	34
7.2	Test Setup	35
7.3	Test Result	35
7.4	Test Setup Photo.....	36
8.	Surge Immunity	37
8.1	Test Specification	37
8.2	Test Setup	37
8.3	Test Result	37
8.4	Test Setup Photo.....	38
9.	Immunity to Conductive Disturbance.....	39
9.1	Test Specification	39
9.2	Test Setup	39
9.3	Test Result	39
9.4	Test Setup Photo.....	40

10.	Power Frequency Magnetic Field immunity	41
10.1	Test Specification.....	41
10.2	Test Setup.....	41
10.3	Test Result.....	41
10.4	Test Setup Photo	42
11.	Voltage Dips, Short Interruption and Voltage Variation immunity	43
11.1	Test Specification.....	43
11.2	Test Setup.....	43
11.3	Test Result.....	43
11.4	Test Setup Photo	44
12.	Harmonics	45
12.1	Test Specification.....	45
12.2	Test Setup.....	45
12.3	Test Result.....	45
12.4	Test Setup Photo	45
13.	Voltage Fluctuations	46
13.1	Test Specification.....	46
13.2	Test Setup.....	46
13.3	Test Result.....	46
13.4	Test Setup Photo	48
14.	Appendix.....	49
14.1	Appendix A: Test Equipment.....	49
14.2	Appendix B: Uncertainty of Measurement	52
14.3	Appendix C: Photographs of EUT Please refer to the File of ISL-13HE041P.....	53

1. General

1.1 Certification of Accuracy of Test Data

Standards:	Please refer to 1.2
Equipment Tested:	Nuvo-2000+ Series
Models:	Nuvo-2021DV+; Nuvo-2030DV+; Nuvo-2021+; Nuvo-2030+
Applicant:	Neosys Technology Inc.
Sample received Date:	February 5, 2013
Final test Date:	EMI: refer to the date of test data EMS: February 22, 2013
Test Site:	International Standards Laboratory OATS 01; Chamber 01; Conduction 01; Immunity01
Test Distance:	10M; 3M (above1GHz) (EMI test)
Temperature:	refer to each site test data
Humidity:	refer to each site test data
Input power:	Conduction input power: AC 230 V / 50 Hz Radiation input power: AC 230 V / 50 Hz Immunity input power: AC 230 V / 50 Hz
Test Result:	PASS
Report Engineer:	Winnie Huang
Test Engineer:	 Stanley Tsai
Approved By:	 Eddy Hsiung

1.2 Test Standards

The tests which this report describes were conducted by an independent electromagnetic compatibility consultant, International Standards Laboratory in accordance with the following

EN 61000-6-4:2007+A1:2011 and IEC 61000-6-4:2006+A1:2010 : Generic standards – Emission Standard for industrial environments.

EN 61000-6-2: 2005 and IEC 61000-6-2: 2005: EMC – Generic standards – Immunity for industrial environments.

EN 55022:2010, CISPR 22:2008 (modified) and: Class A: Limits and methods of measurement of Radio Interference characteristics of Information Technology Equipment.

EN 55024:2010 and CISPR 24:2010: Information technology equipment-Immunity characteristics - Limits and methods of measurement.

Standard	Description	Results	Criteria
EN 61000-4-2:2009 IEC 61000-4-2:2008	Electrostatic Discharge	Pass	B
EN 61000-4-3:2006+A1:2008 +A2:2010 IEC 61000-4-3:2006+A1:2007+A2:2010	Radio-Frequency, Electromagnetic Field	Pass	A
EN 61000-4-4: 2004 +A1:2010 IEC 61000-4-4: 2004 +A1:2010	Electrical Fast Transient/Burst	Pass	B
EN 61000-4-5: 2006 IEC 61000-4-5: 2005	Surge	Pass	B
EN 61000-4-6:2009 IEC 61000-4-6:2008	Conductive Disturbance	Pass	A
EN 61000-4-8:2010 IEC 61000-4-8:2009	Power Frequency Magnetic Field	Pass	A
EN 61000-4-11: 2004 IEC 61000-4-11: 2004	Voltage Dips / Short Interruption and Voltage Variation		
	100% in 20ms	Pass	B
	30% in 500ms	Pass	C
	60% in 2000ms	Pass	C
	100% in 5000ms	Pass	C

Standard	Description	Results
EN 61000-3-2: 2006 +A1:2009 +A2:2009 IEC 61000-3-2: 2005 +A1:2008 +A2:2009	Limits for harmonics current emissions	Pass
EN 61000-3-3: 2008 IEC 61000-3-3: 2008	Limits for voltage fluctuations and flicker in low-voltage supply systems.	Pass

1.2.1 Criteria for Compliance: EN 55024

Performance criterion A

During and after the test the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a minimum performance level specified by the manufacturer when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

Performance criterion B

After the test, the EUT shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the EUT is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is allowed. However, no change of operating state or stored data is allowed to persist after the test. If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the EUT if used as intended.

Performance criterion C

During and after testing, a temporary loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls or cycling of the power to the EUT by the user in accordance with the manufacturer's instructions.

Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be lost.

1.2.2 Criteria for Compliance: EN 61000-6-2

Performance criterion A

The apparatus shall continue to operate as intended during and after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

Performance criterion B

The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed. No change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation and what the user may reasonably expect from the apparatus if used as intended.

Performance criterion C

Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

1.3 Description of EUT

EUT

Product Name	Nuvo-2000+ Series
Condition	Pre-Production
Model Numbers	Nuvo-2021DV+; Nuvo-2030DV+; Nuvo-2021+; Nuvo-2030+
Serial Number	N/A
Power Supply	STARMEN (Model: TFS060120)
	AC input: 100-240V~50/60Hz Max 1.6A
	DC output: 12V---5A
	Total output wattage: 60W MAX
CPU	Intel® Atom™ processor D525 (1M Cache, 1.8GHz)
Motherboard	Model: NVS-2000+
SATA Hard Disk	TOSHIBA (Model: MQ01ABD032) 320GB 5400RPM*2
Memory	DSL DDR3 1333 4GB
Compact Flash Card:	Apacer 8GB
VGA Port	two 15-pins
USB 2.0 Port	four 4-pins
RJ45 Port	two 8-pins (10/100/1000Mbps)
COM Port	three 9-pins
Microphone Port	one
Line-out Port	one
DC-In(12V)	one
DC-In(8~25V)	one
Power button	one
Maximum Resolution	1920*1080
Maximum Operating Frequency	1.8GHz

All types of configurations have been tested. We present the worst case test data (configuration1) in the report. The test configurations are listed below:

For Radiation & Conduction LISN & EMS

Configurations	Display	RJ45 Port	Power Supply
1	Dual VGA(Clone):1024*768+1024*768	two RJ45 Ports simultaneous transmission(1000M bps)	STARMEN (Model: TFS060120)
2	Dual VGA(Extended):1920*1080+1024*768	two RJ45 Ports simultaneous transmission(1000M bps)	STARMEN (Model: TFS060120)
3	Single VGA: 1920*1080	two RJ45 Ports simultaneous transmission(1000M bps)	STARMEN (Model: TFS060120)
4	Dual VGA(Clone):1024*768+1024*768	two RJ45 Ports simultaneous transmission(1000M bps)	DC Power Supply

For Conduction ISN:

Configurations	Display	RJ45 Port	Power Supply
1	Dual VGA(Clone):1024*768+1024*768	RJ45 Port1(10/100/1000 Mbps)	STARMEN (Model: TFS060120)
2	Dual VGA(Clone):1024*768+1024*768	RJ45 Port2(1000Mbps)	STARMEN (Model: TFS060120)

Model Differences:

	PCIE(1x PCIE + 2x PCI slot)	No PCIE(3x PCI slot)
One VGA	Nuvo-2021+	Nuvo-2030+
Two VGA	Nuvo-2021DV+ Series	Nuvo-2030DV+

EMI Noise Source

Motherboard Crystal	27MHz (X1)
	25MHz (X2)
	25MHz (X3)
	32.768KHz(X4)
	14.318MHz (X5)

EMI Solution

Solution	Quantity	Location
Core	1	The same as Photo EUT-6
Gaskets	2	The same as Photo EUT-7 Mark1,2

1.4 Description of Support Equipment

Unit	Model Serial No.	Brand	Power Cord	FCC ID
Notebook Personal Computer	STUDIO 17 S/N: N/A	DELL	Non-shielded, Detachable	FCC DOC
Rack mountable Switch	DGS-1008D	D-Link	D-Link (Model:AF-1205 -B)	FCC DOC
24" LED Monitor	ST2420L S/N: S/N:CN-0X0K27-74261-2 7E-131U	DELL	Non-shielded, Detachable	FCC DOC
USB2.0 External HDD Enclosure *2	Ipod nano S/N: N/A	Apple	N/A	FCC DOC
Keyboard	SK-8115, S/N: MY-05N456-38843-2BK- 3315	DELL	N/A	FCC DOC
Mouse	MO71KC S/N: 511092011	DELL	N/A	FCC DOC
Headphone & Microphone	CD-85	JS	N/A	FCC DOC
Modem	DM1414 S/N: 0301000557	Aceex	Non-shielded, Without Grounding Pin	IFAXDM1414

1.5 Software for Controlling Support Unit

Test programs exercising various part of EUT were used. The programs were executed as follows:

- A. Send H pattern to the video port device (Monitor).
- B. Read and write to the disk drives.
- C. Send H pattern to the serial port device (Modem).
- D. Send package to the Router RJ45 port (Router)
- E. Receive and transmit package of EUT to the Rack mountable Switch HUB through RJ45 port.
- F. Used Tfggen.exe to send signal to EUT RJ45 port through Notebook Personal Computer RJ45 Port.
- G. Read and write data in the USB2.0 Hard Disk through EUT USB2.0 port.
- H. Send audio signal to the Microphone and HeadSet through Headphone port
- I. Receive audio signal from Microphone and HeadSet through Microphone port
- J. Repeat the above steps.

	Filename	Issued Date
Monitor	Intel EMC TEST.exe	9/04/2000
RJ45	ping.exe	05/05/1999
RJ45	Tfggen.exe	06/23/1999
Modem	Intel EMC TEST.exe	9/04/2000
USB2.0 External HDD Enclosure	Intel EMC TEST.exe	9/04/2000
EUT Hard Disk	Intel EMC TEST.exe	9/04/2000
Headphone & Microphone	Windows Media player.exe	2006/2/18


1.6 I/O Cable Condition of EUT and Support Units

Description	Path	Cable Length	Cable Type	Connector Type
DC-In(DC 12V)	Power Supply (ADAPTER) to EUT DC-In(DC 12V)Port	1.2M	Non-shielded, Detachable	Metal Head
DC-In(DC 8~25V)	with dummy	0.3M	Non-shielded, Detachable	Plastic Head
RJ45 Data Cable	Notebook Personal Computer RJ45 Port to Switch Hub RJ45 Port	2.0M	Non-shielded, Detachable	Plastic Head
RJ45 Data Cable*2	Switch Hub RJ45 Port to EUT RJ45 Port	10M	Non-shielded, Detachable	Plastic Head
Display Data Cable*2	EUT VGA Port to LCD Monitor VGA Port	1.8M	Shielded, Detachable	Metal Head
Modem Data Cable	Modem to EUT COM Port	1.5M	Non-shielded, Detachable	Metal Head
Headphone & Microphone Data Cable*	Headphone & Microphone to EUT line out port and line in port	1.9M	Non-shielded, Un-detachable	Plastic Head
Keyboard Data Cable	Keyboard to EUT USB2.0 Port	2.0M	Non-shielded, Un-detachable	Metal Head
Mouse Data Cable	Mouse to EUT USB2.0 Port	1.8M	Non-shielded, Un-detachable	Metal Head

2. Power Main Port Conducted Emissions

2.1 Test Setup and Procedure

2.1.1 Test Setup



2.1.2 Test Procedure

The measurements are performed in a 3.5m x 3.4m x 2.5m shielded room, which referred as Conduction 01 test site, or a 3m x 3m x 2.3m test site, which referred as Conduction 02 test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

The interconnecting cables were arranged and moved to get the maximum measurement. Both the line of power cord, hot and neutral, were measured.


The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

2.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	150KHz--30MHz
Detector Function:	Quasi-Peak / Average Mode
Resolution Bandwidth:	9KHz

2.2 Conduction Test Data: Configuration 1

Table 2.2.1 Power Line Conducted Emissions (Hot)



No.	Frequency MHz	LISN Loss dB	Cable Loss dB	QP Correct. dBuV	QP Limit dBuV	QP Margin dB	AVG Correct. dBuV	AVG Limit dBuV	AVG Margin dB	Note
1	0.1556	9.32	0.02	43.92	79.00	-35.08	26.13	66.00	-39.87	
2	0.1640	9.40	0.02	49.32	79.00	-29.68	34.03	66.00	-31.97	
3	0.1780	9.53	0.02	47.84	79.00	-31.16	31.19	66.00	-34.81	
4	0.2021	9.74	0.02	43.96	79.00	-35.04	29.13	66.00	-36.87	
5	0.2130	9.74	0.02	44.18	79.00	-34.82	31.87	66.00	-34.13	
6	5.2250	9.66	0.20	40.56	73.00	-32.44	35.43	60.00	-24.57	

Note:

Margin = Corrected Amplitude - Limit

Corrected Amplitude = Receiver Reading + LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit


The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

Table 2.2.2 Power Line Conducted Emissions (Neutral)



Test LAB: International Standards Laboratory (Hsichih Site)
Tel: 886-2-26462550
Fax: 886-2-26464641



No.	Frequency MHz	LISN Loss dB	Cable Loss dB	QP Correct. dBuV	QP Limit dBuV	QP Margin dB	AVG Correct. dBuV	AVG Limit dBuV	AVG Margin dB	Note
1	0.1514	9.97	0.02	43.64	79.00	-35.36	22.36	66.00	-43.64	
2	0.1570	9.95	0.02	45.61	79.00	-33.39	28.24	66.00	-37.76	
3	0.1636	9.91	0.02	49.30	79.00	-29.70	33.97	66.00	-32.03	
4	0.1727	9.87	0.02	48.80	79.00	-30.20	34.30	66.00	-31.70	
5	0.1870	9.79	0.02	43.59	79.00	-35.41	27.56	66.00	-38.44	
6	5.1750	9.61	0.20	39.98	73.00	-33.02	35.13	60.00	-24.87	

Note:

Margin = Corrected Amplitude - Limit

Corrected Amplitude = Receiver Reading + LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

2.3 Test Setup Photo


Front View



Back View



3.1.1 Test Setup




3.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range: 150KHz--30MHz
 Detector Function: Quasi-Peak / Average Mode
 Resolution Bandwidth: 9KHz

3.2 Test Data: LAN--10M: Configuration 1

Table 3.2.1 Telecommunication Port Conducted Emission



No.	Frequency MHz	LISN Loss dB	Cable Loss dB	QP Correct. dBuV	QP Limit dBuV	QP Margin dB	AVG Correct. dBuV	AVG Limit dBuV	AVG Margin dB	Note
1	6.2250	9.96	0.21	41.51	87.00	-45.49	34.54	74.00	-39.46	
2	7.5000	9.96	0.23	61.81	87.00	-25.19	49.94	74.00	-24.06	
3	8.7500	9.96	0.24	56.15	87.00	-30.85	44.61	74.00	-29.39	
4	9.9500	9.96	0.25	45.15	87.00	-41.85	38.18	74.00	-35.82	
5	11.2500	9.96	0.26	56.15	87.00	-30.85	45.61	74.00	-28.39	
6	12.5000	9.96	0.27	58.23	87.00	-28.77	46.54	74.00	-27.46	

Note :

Margin = Corrected Amplitude - Limit

Corrected Amplitude = Receiver Reading + LISN Loss + Cable Loss


A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

3.3 Test Data: LAN--100M: Configuration 1

Table 3.3.1 Telecommunication Port Conducted Emission



No.	Frequency MHz	LISN Loss dB	Cable Loss dB	QP Correct. dBuV	QP Limit dBuV	QP Margin dB	AVG Correct. dBuV	AVG Limit dBuV	AVG Margin dB	Note
1	5.2250	9.96	0.20	53.46	87.00	-33.54	48.45	74.00	-25.55	
2	10.8000	9.96	0.26	45.33	87.00	-41.67	41.73	74.00	-32.27	
3	16.2250	9.96	0.30	56.97	87.00	-30.03	53.75	74.00	-20.25	
4	18.2500	9.97	0.32	49.51	87.00	-37.49	47.19	74.00	-26.81	
5	20.2750	9.97	0.33	44.60	87.00	-42.40	29.82	74.00	-44.18	
6	23.1250	9.98	0.35	59.47	87.00	-27.53	56.69	74.00	-17.31	

Note :

Margin = Corrected Amplitude - Limit

Corrected Amplitude = Receiver Reading + LISN Loss + Cable Loss


A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

3.4 Test Data: LAN--GIGA: Configuration 1

Table 3.4.1 Telecommunication Port Conducted Emission



No.	Frequency MHz	LISN Loss dB	Cable Loss dB	QP Correct. dBuV	QP Limit dBuV	QP Margin dB	AVG Correct. dBuV	AVG Limit dBuV	AVG Margin dB	Note
1	3.3710	9.92	0.17	47.38	87.00	-39.62	42.53	74.00	-31.47	
2	5.1250	9.93	0.20	54.51	87.00	-32.49	49.58	74.00	-24.42	
3	6.4500	9.95	0.22	44.18	87.00	-42.82	38.80	74.00	-35.20	
4	7.0750	9.96	0.23	44.43	87.00	-42.57	39.30	74.00	-34.70	
5	12.9750	10.05	0.27	47.02	87.00	-39.98	43.82	74.00	-30.18	
6	19.4250	10.11	0.33	44.65	87.00	-42.35	40.95	74.00	-33.05	

Note :

Margin = Corrected Amplitude - Limit

Corrected Amplitude = Receiver Reading + LISN Loss + Cable Loss


A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.

3.5 Test Data: LAN--GIGA: Configuration 2

Table 3.5.1 Telecommunication Port Conducted Emission



No.	Frequency MHz	LISN Loss dB	Cable Loss dB	QP Correct. dBuV	QP Limit dBuV	QP Margin dB	AVG Correct. dBuV	AVG Limit dBuV	AVG Margin dB	Note
1	3.6635	9.93	0.17	45.52	87.00	-41.48	40.38	74.00	-33.62	
2	5.1500	9.93	0.20	49.40	87.00	-37.60	40.38	74.00	-33.62	
3	6.4750	9.95	0.22	41.61	87.00	-45.39	36.68	74.00	-37.32	
4	10.7500	10.02	0.26	42.39	87.00	-44.61	36.70	74.00	-37.30	
5	12.9750	10.05	0.27	46.17	87.00	-40.83	40.56	74.00	-33.44	
6	19.4250	10.11	0.33	44.56	87.00	-42.44	36.66	74.00	-37.34	

Note :

Margin = Corrected Amplitude - Limit

Corrected Amplitude = Receiver Reading + LISN Loss + Cable Loss

A margin of -8dB means that the emission is 8dB below the limit

The frequency spectrum graph is for final peak graph, and the attached table is for QP/AVG test result.

If peak data can pass, it will be shown in "QP/AVG Correct" column, if not, QP/AVG data will instead.


3.6 Test Setup Photo

Refer to the Setup Photos for Power Main Port Conducted Emissions

4. Radiated Disturbance Emissions

4.1 Test Setup and Procedure

4.1.1 Test Setup



4.1.2 Test Procedure

The radiated emissions test will then be repeated on the open site or chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of 10 meter open field sites or 10 meter chamber. Desktop EUT are set up on a wooden stand 0.8 meter above the ground or floor-standing arrangement shall be placed on the horizontal ground reference plane. The test volume for a height of up to 30 cm may be obstructed by absorber placed on the ground plane.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. The highest emissions between 30 MHz to 1000 MHz were analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. The highest emissions between 1 GHz to 6 GHz were analyzed in details by operating the spectrum analyzer in peak and average mode to determine the precise amplitude of the emissions.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum measurement. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings.

The highest internal source of an EUT is defined as the highest frequency generated or used within the EUT or on which the EUT operates or tunes. If the highest frequency of the internal sources of the EUT is less than 108 MHz, the measurement shall only be made up to 1 GHz. If the highest frequency of the internal sources of the EUT is between 108 MHz and 500 MHz, the measurement shall only be made up to 2 GHz. If the highest frequency of the internal sources of the EUT is between 500 MHz and 1 GHz, the measurement shall only be made up to 5 GHz. If the highest frequency of the internal sources of the EUT is above 1 GHz, the measurement shall be made up to 5 times the highest frequency or 6 GHz, whichever is less.

4.1.3 Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range:	30MHz--1000MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth:	120KHz


Frequency Range:	Above 1 GHz to 6 GHz
Detector Function:	Peak/Average Mode
Resolution Bandwidth:	1MHz

4.2 Radiation Test Data: Configuration 1

Table 4.2.1 Radiated Emissions (Horizontal)



Test LAB: International Standards Laboratory (Hsichih Site)
Tel: 886-2-26462550
Fax: 886-2-26464641



Mk.	Frequency (MHz)	RX_R (dBuV/m)	Ant_F (dB)	Cab_L (dB)	PreAmp (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	215.2700	22.08	10.61	1.47	0.00	34.16	40.00	-5.84	381	249	QP
2	221.0900	22.32	10.84	1.48	0.00	34.64	40.00	-5.36	333	172	QP
3	226.9100	22.59	11.08	1.51	0.00	35.18	40.00	-4.82	321	78	QP
4	461.6500	20.53	17.31	2.22	0.00	40.06	47.00	-6.94	215	209	QP
5	601.3300	19.86	18.63	2.54	0.00	40.93	47.00	-6.07	100	19	QP
6	801.1500	17.67	21.42	2.98	0.00	42.07	47.00	-4.93	306	344	QP

* Note:

Margin = Corrected Amplitude – Limit

Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

BILOG Antenna Distance: 10 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.




Test LAB: International Standards Laboratory (Hsichih Site)
Tel: 886-2-26462550
Fax: 886-2-26464641

Radiated Emission Measurement

Date: 2013/2/6
Time: PM 01:11:48

Operator:
Temperature: 25 °C
Humidity: 55 %



Site : Chamber 01

Condition : CISPR22 ClassA Radiation

Polarization: *Horizontal*

Mk.	Frequency (MHz)	RX_R (dBuV/m)	Ant_F (dB)	Cab_L (dB)	PreAmp (dB)	Correct. (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1272.436	66.39	28.3	3.27	51.9	0	46.06	76.00	-29.94	154	199	peak
2	1600.033	77.26	28.86	3.7	51.97	0	57.85	76.00	-18.15	124	20	peak
3	1600.033	74.95	28.86	3.7	51.97	0	55.54	56.00	-0.46	100	63	AVG
4	1721.154	68.40	29.54	3.84	51.99	0	49.79	76.00	-26.21	100	303	peak
5	1921.474	63.82	30.87	4.08	52.03	0	46.74	76.00	-29.26	183	74	peak
6	2434.295	67.72	31.89	4.65	52	0	52.26	76.00	-23.74	100	311	peak
7	2995.192	62.15	32.59	5.21	52.07	0	47.88	76.00	-28.12	100	249	peak

*:Maximum data x:Over limit !:over margin

* Note:

Margin = Corrected Amplitude – Limit

Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit


Horn Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

Table 4.2.2 Radiated Emissions (Vertical)



Test LAB: International Standards Laboratory (Hsichih Site)
Tel: 886-2-26462650
Fax: 886-2-26464641



Mk.	Frequency (MHz)	RX_R (dBuV/m)	Ant_F (dB)	Cab_L (dB)	PreAmp (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	30.0000	14.35	21.3	0.58	0.00	36.23	40.00	-3.77	139	141	QP
2	42.6100	23.51	12.22	0.68	0.00	36.41	40.00	-3.59	131	215	QP
3	86.2600	27.40	7.8	0.93	0.00	36.13	40.00	-3.87	284	231	QP
4	221.0900	23.67	10.84	1.48	0.00	35.99	40.00	-4.01	100	283	QP
5	226.9100	23.84	11.08	1.51	0.00	36.43	40.00	-3.57	306	35	QP
6	461.6500	22.95	17.31	2.22	0.00	42.48	47.00	-4.52	394	136	QP

* Note:

Margin = Corrected Amplitude – Limit

Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

BILOG Antenna Distance: 10 meters

Below 1GHz test, if the peak measured value meets the QP limit, it is unnecessary to perform the QP measurement.




Test LAB: International Standards Laboratory (Hsichih Site)
Tel: 886-2-26462550
Fax: 886-2-26464641

Radiated Emission Measurement

Date: 2013/2/6
Time: PM 01:46:48

Operator:
Temperature: 25 °C
Humidity: 55 %



Site : Chamber 01

Condition : CISPR22 ClassA Radiation

Polarization: *Vertical*

Mk.	Frequency (MHz)	RX_R (dBuV/m)	Ant_F (dB)	Cab_L (dB)	PreAmp (dB)	Correct. (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Ant.Pos (cm)	Tab.Pos (deg.)	Detector
1	1600.962	73.52	28.87	3.7	51.97	0	54.12	76.00	-21.88	154	324	peak
2	1721.154	61.57	29.54	3.84	51.99	0	42.96	76.00	-33.04	154	358	peak
3	1921.474	63.52	30.87	4.08	52.03	0	46.44	76.00	-29.56	122	97	peak
4	2065.705	61.48	31.45	4.24	52.03	0	45.14	76.00	-30.86	132	65	peak
5	2434.295	62.44	31.89	4.65	52	0	46.98	76.00	-29.02	168	260	peak
6	2714.744	60.40	32.26	4.93	52.02	0	45.57	76.00	-30.43	100	186	peak

^:Maximum data x:Over limit !:over margin

* Note:

Margin = Corrected Amplitude – Limit

Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss – Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

Horn Antenna Distance: 3 meters

Above 1GHz test, if the peak measured value meets the average limit, it is unnecessary to perform the average measurement.

4.3 Test Setup Photo


Front View (30MHz~1GHz)




Back View (30MHz~1GHz)



Front View (above 1GHz)



Back View (above 1GHz)



5. Electrostatic discharge (ESD) immunity

5.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-2/ IEC 61000-4-2 (details referred to Sec 1.2)
Test Level:	Air +/- 2 kV, +/- 4 kV, +/- 8 kV Contact +/- 2 kV, +/- 4 kV
Criteria:	B
Test Procedure	refer to ISL QA -T4-E-S7
Temperature:	18°C
Humidity:	50%

Selected Test Point


Air: discharges were applied to slots, aperture or insulating surfaces. 10 single air discharges were applied to each selected points.

Contact: Total 200 discharges minimum were to the selected contact points.

Indirect Contact Points: 25 discharges were applied to center of one edge of VCP and each EUT side of HCP with 10 cm away from EUT.

5.2 Test Setup

EUT is 1m from the wall and other metallic structure. When Battery test mode is needed, a cable with one 470KΩ resistor at two rare ends is connected from metallic part of EUT and screwed to HCP.




5.3 Test Result

Performance of EUT complies with the given specification.

5.4 Test Point

Red arrow lines indicate the contact points, and blue arrow lines indicate the air points.



5.5 Test Setup Photo




6. Radio-Frequency, Electromagnetic Field immunity

6.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-3/ IEC 61000-4-3 (details referred to Sec 1.2)
Test Level:	10 V/m; 3 V/m; 1 V/m
Modulation:	AM 1KHz 80%
Frequency range:	80 MHz~1 GHz; 1.4G~2.0GHz; 2.0G~2.7GHz
Frequency Step:	1% of last step frequency
Dwell time:	800 ms
Polarization:	Vertical and Horizontal
EUT Azimuth Angle	☒0° ☒90° ☒180° ☒270°
Criteria:	A
Test Procedure	refer to ISL QA -T4-E-S8
Temperature:	18 °C
Humidity:	50%

6.2 Test Setup


The field sensor is placed at one calibration grid point to check the intensity of the established fields on both polarizations. EUT is adjusted to have each side of EUT face coincident with the calibration plane. A CCD camera and speakers are used to monitor the condition of EUT for the performance judgment.



6.3 Test Result

Performance of EUT complies with the given specification.

6.4 Test Setup Photo



7. Electrical Fast transients/burst immunity

7.1 Test Specification

Port:	AC mains; Twisted Pair LAN Port
Basic Standard:	EN 61000-4-4/ IEC 61000-4-4 (details referred to Sec 1.2)
Test Level:	AC Power Port: +/- 2 kV Twisted Pair LAN Port(I/O cable): +/- 1 kV
Rise Time:	5ns
Hold Time:	50ns
Repetition Frequency:	5KHz
Criteria:	B
Test Procedure	refer to ISL QA -T4-E-S9
Temperature:	18 °C
Humidity:	50%

Test Procedure



The EUT was setup on a nonconductive table 0.1 m above a reference ground plane.

Test Points	Polarity	Result	Comment
Line	+	N	60 sec
	-	N	60 sec
Neutral	+	N	60 sec
	-	N	60 sec
Ground	+	N	60 sec
	-	N	60 sec
Line to Neutral	+	N	60 sec
	-	N	60 sec
Line to Ground	+	N	60 sec
	-	N	60 sec
Neutral to Ground	+	N	60 sec
	-	N	60 sec
Line to Neutral to Ground	+	N	60 sec
	-	N	60 sec
Capacitive coupling clamp	+	N	60 sec
	-	N	60 sec

Note: 'N' means normal, the EUT function is correct during the test.

7.2 Test Setup

EUT is at least 50cm from the conductive structure.



7.3 Test Result

Performance of EUT complies with the given specification.

7.4 Test Setup Photo




8. Surge Immunity

8.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-5/ IEC EN61000-4-5 (details referred to Sec 1.2)
Test Level:	Line to Line: +/- 0.5 kV, +/- 1 kV Line to Earth: +/- 0.5 kV, +/- 1 kV, +/- 2kV
Rise Time:	1.2us
Hold Time:	50us
Repetition Rate:	30 second
Angle:	☒0° ☒90° ☒180° ☒270°
Criteria:	B
Test Procedure:	refer to ISL QA -T4-E-S10
Temperature:	19°C
Humidity:	56%

8.2 Test Setup



8.3 Test Result

Performance of EUT complies with the given specification.

8.4 Test Setup Photo




9. Immunity to Conductive Disturbance

9.1 Test Specification

Port:	AC mains; Twisted Pair LAN Port
Basic Standard:	EN 61000-4-6/ IEC 61000-4-6 (details referred to Sec 1.2)
Test Level:	10V
Modulation:	AM 1KHz 80%
Frequency range:	0.15 MHz - 80MHz
Frequency Step:	1% of last Frequency
Dwell time:	3S
Criteria:	A
CDN Type:	CDN M2+M3, CDN T2, CDN T4, CDN T8, EM Clamp
Test Procedure	refer to ISL QA -T4-E-S11
Temperature:	18°C
Humidity:	50%

9.2 Test Setup



9.3 Test Result

Performance of EUT complies with the given specification.

9.4 Test Setup Photo




10. Power Frequency Magnetic Field immunity

10.1 Test Specification

Port:	Enclosure
Basic Standard:	EN 61000-4-8/ IEC 61000-4-8 (details referred to Sec 1.2)
Test Level:	30A/m
Polarization:	X, Y, Z
Criteria:	A
Test Procedure	refer to ISL QA -T4-E-S12
Temperature:	18°C
Humidity:	50%

10.2 Test Setup



10.3 Test Result

Performance of EUT complies with the given specification.

10.4 Test Setup Photo




11. Voltage Dips, Short Interruption and Voltage Variation immunity

11.1 Test Specification

Port:	AC mains
Basic Standard:	EN 61000-4-11/ IEC 61000-4-11 (details referred to Sec 1.2)
Test Level: Criteria:	100% in 20ms B
Test Level: Criteria:	30% in 500ms C
Test Level: Criteria:	60% in 200ms C
Test Level: Criteria:	100% in 5000ms C
Phase:	0°; 180°
Test intervals:	3 times with 10s each
Test Procedure	refer to ISL QA -T4-E-S13
Temperature:	18°C
Humidity:	50%

11.2 Test Setup



11.3 Test Result

Performance of EUT complies with the given specification.

11.4 Test Setup Photo



12. Harmonics

12.1 Test Specification


Port:	AC mains
Active Input Power:	<75W
Basic Standard:	EN61000-3-2/IEC 61000-3-2 (details referred to Sec 1.2)
Test Duration:	2.5min
Class:	D
Test Procedure	refer to ISL QA -T4-E-S14
Temperature:	19°C
Humidity:	56%

Test Procedure

The EUT is supplied in series with shunts or current transformers from a source having the same nominal voltage and frequency as the rated supply voltage and frequency of the EUT. The EUT is configured to its rated current with additional resistive load when the testing is performed.

Equipment having more than one rated voltage shall be tested at the rated voltage producing the highest harmonics as compared with the limits.

12.2 Test Setup



12.3 Test Result

Active input power under 75W, no limit apply, declare compliance

12.4 Test Setup Photo

Refer to the Setup Photo for Voltage Fluctuations

13. Voltage Fluctuations


13.1 Test Specification

Port:	AC mains
Basic Standard:	EN61000-3-3/IEC61000-3-3 (details referred to Sec 1.2)
Test Procedure	refer to ISL QA -T4-E-S14
Observation period:	For Pst 10min
	For Plt 2 hours
Temperature:	19°C
Humidity:	56%

Test Procedure

The EUT is supplied in series with reference impedance from a power source with the voltage and frequency as the nominal supply voltage and frequency of the EUT.

13.2 Test Setup




13.3 Test Result

Performance of EUT complies with the given specification.

Test Data:

10Min

Flickermeter 1000-4-15 for 230V/50Hz

**Flicker Emission - IEC 61000-3-3 , EN 61000-3-3 , (EN60555-3)**

U_{rms} = 229.9 V P = 20.91 W
 I_{rms} = 0.224 A pf = 0.407

2013/2/6 AM 10:14:51


Range: 2 A
 V-nom: 230 V
 TestTime: 10 min (100%)

Test completed, Result: PASSED

HAR-1000 EMC-Retester

120Min

Flickermeter 1000-4-15 for 230V/50Hz

**Flicker Emission - IEC 61000-3-3 , EN 61000-3-3 , (EN60555-3)**

U_{rms} = 229.9 V P = 20.62 W
 I_{rms} = 0.222 A pf = 0.404

2013/2/6 PM 12:32:45

Range: 2 A
 V-nom: 230 V
 TestTime: 120 min (10000%)

Test completed, Result: PASSED

HAR-1000 EMC-Retester

13.4 Test Setup Photo



14. Appendix

14.1 Appendix A: Test Equipment

14.1.1 Test Equipment List

Location CON01	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction	Coaxial Cable 1F-C1	EMEC	5D Cable	1F-C1	10/26/2012	10/26/2013
Conduction	LISN 21	ROHDE & SCHWARZ	ENV216	101476	05/10/2012	05/10/2013
Conduction	LISN 22	ROHDE & SCHWARZ	ENV216	101478	05/10/2012	05/10/2013
Conduction	ISN T2 03	FCC	FCC-TLISN-T 2-02	20618	08/03/2012	08/03/2013
Conduction	ISN T4 05	FCC	FCC-TLISN-T 4-02	20619	08/03/2012	08/03/2013
Conduction	ISN T8 03	FCC	FCC-TLINS-T 8-02	20620	08/03/2012	08/03/2013
Conduction	ISN T8 06 (Shielding)	Teseq GmbH	ISN ST08	33999	08/09/2012	08/09/2013
Conduction	EMI Receiver 15	ROHDE & SCHWARZ	ESCI	101166	04/24/2012	04/24/2013

Location OATS01	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Radiation	BILOG Antenna 10	Sumol Sciences	JB1	A013004-1	07/18/2012	07/18/2013
Radiation	Coaxial Cable 3F-10M	EMCI	CFD400-NL	ISL-R001	03/16/2012	03/16/2013
Radiation	EMI Receiver 13	ROHDE & SCHWARZ	ESCI	101015	02/22/2012	02/22/2013

Location Chamber 01	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Rad. above 1Ghz	Horn Antenna 11	ETS-LINDGR EN	3117	00114397	03/07/2012	03/07/2013
Rad. above 1Ghz	Horn Antenna 03	COM-Power	AH-826	100A	03/15/2011	03/15/2013
Rad. above 1Ghz	Horn Antenna 05	Com-Power	AH-640	100A	01/11/2013	01/11/2015
Rad. above 1Ghz	Microwave Cable-16	HUBER SUHNER	SUCFLEX 104	345761/4	12/24/2012	12/24/2013
Rad. above 1Ghz	Preamplifier 20	EMCI	EMC051845	980084	10/30/2012	10/30/2013
Rad. above 1Ghz	Microwave Cable-19	HUBER SUHNER	SUCFLEX 102	MY 2151/2	05/03/2012	05/03/2013
Rad. above 1Ghz	Preamplifier 22	EMCI	EMC184045	980124	04/02/2012	04/02/2013
Rad. above 1Ghz	Spectrum Analyzer 23	ROHDE & SCHWARZ	FSU43	101255	11/01/2012	11/01/2013

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
EN61K-3-2/3	DC Burn-In Load 02	D-RAM	DBS-2100	2100-910027	N/A	N/A
EN61K-3-2/3	Harmonic/Flicker Test System 03	EMC Partner	HARMONICS-1000	178	03/23/2012	03/23/2013
EN61K-4-,4,5,8,11	TRANSIENT 2000 01	EMC Partner	TRANSIENT-2000	950	12/01/2012	12/01/2013
EN61K-4-2	ESD GUN 09	EM TEST AG.	Dito	V1018106503	05/12/2012	05/12/2013
EN61K-4-3	BILOG Antenna 06	Schaffner	CBL6112B	2754	N/A	N/A
EN61K-4-3	Amplifier 80Mz~1GHz 250W	AR	250W1000A	312494	N/A	N/A
EN61K-4-3	Amplifier 800MHz~3.0GHz 60W	AR	60S1G3	312762	N/A	N/A
EN61K-4-3	Broadband coupler 10K~220Mhz	Amplifier Research	DC2500	19810	N/A	N/A
EN61K-4-3	Broadband Coupler 80M~1GHz	Amplifier Research	DC6180	20364	N/A	N/A
EN61K-4-3	Broadband Coupler 1~4GHz	Werlatone	C5291	6516	N/A	N/A
EN61K-4-3	Coaxial Cable Chmb 04-3M-2	Belden	RG-8/U	Chmb 04-3M-2	N/A	N/A
EN61K-4-3	Signal Generator 03	Anritsu	MG3642A	6200162550	06/26/2012	06/26/2013
EN61K-4-4	Digital Oscilloscope	Tektronix	TDS 684A	B010761	N/A	N/A
EN61K-4-4	EFT Clamp	Precision	1604242	CNEFT1000-103	N/A	N/A
EN61K-4-5	CDN-UTP8 01	EMC Partner	CDN-UTP8	032	12/01/2012	12/01/2013
EN61K-4-5	SURGE-TESTER 01	EMC Partner	MIG0603IN3	778	12/01/2012	12/01/2013
EN61K-4-6	6dB Attenuator	Weinschel Corp	33-6-34	BC5975	N/A	N/A
EN61K-4-6	Amplifier 4-6	Amplifier Research	150A100	1-1-R-02157	N/A	N/A
EN61K-4-6	Attenuator 6dB 4-6	BIRO	100-A-FFN-06	0123	N/A	N/A
EN61K-4-6	CDN M2+M3	Frankonia	M2+M3	A3011016	07/31/2012	07/31/2013
EN61K-4-6	CDN T2 01	Frankonia	T2	A3010003	07/31/2012	07/31/2013
EN61K-4-6	CDN T4 05	FCC Inc.	FCC-801-T4-RJ45	08020	09/01/2012	09/01/2013
EN61K-4-6	CDN T8 01	FCC Inc.	FCC-801-T8-RJ45	08021	09/01/2012	09/01/2013
EN61K-4-6	CDN RJ45S 01	Frankonia	CDN-RJ45/S	A3150047	10/15/2012	10/15/2013
EN61K-4-6	EM-Clamp 01	FCC	F-203I-23MM	539	N/A	N/A
EN61K-4-6	Coaxial Cable 4-6 01-1	Harbour Industries	M17/128-RG400	4-6 01-1	N/A	N/A
EN61K-4-6	Coaxial Cable 4-6 01-2	Harbour Industries	M17/128-RG400	4-6 01-2	N/A	N/A
EN61K-4-6	Coaxial Cable 4-6 01-3	Harbour Industries	M17/128-RG400	4-6 01-3	N/A	N/A
EN61K-4-6	KAL-AD RJ45S	BIRO			N/A	N/A
EN61K-4-6	KAL-AD T2	BIRO			N/A	N/A
EN61K-4-6	Passive Impedance Adaptor 4-6	FCC	FCC-801-150-50-CDN	9758;9759	N/A	N/A
EN61K-4-6, CISPR 13, Antenna	Signal Generator 02	HP	8648B	3642U01040	08/28/2012	08/28/2013
EN61K-4-8	Magnetic Field Antenna	Precision	TRAIZ44B	MF1000-23	N/A	N/A

PS: N/A => The equipment does not need calibration.

14.1.2 Software for Controlling Spectrum/Receiver and Calculating Test Data

Test Item	Filename	Version
EN61000-3-2	HARCS.EXE	4.16
EN61000-3-3	HARCS.EXE	4.16
EN61000-4-2	N/A	2.0
EN61000-4-3	Tile.Exe	2.0.P
EN61000-4-4	Tema.EXE	1.69
EN61000-4-5	Tema.EXE	1.69
EN61000-4-6	EN61000-4-6 Application Software	1.13.e
EN61000-4-8	N/A	
EN61000-4-11	VDS-2002Rs.EXE	2.00

Radiation/Conduction	Filename	Version	Issued Date
Hsichih Conduction	EZ EMC	1.1.4.2	2/10/2007
Hsichih Radiation	EZ EMC	1.1.4.2	1/24/2007

14.2 Appendix B: Uncertainty of Measurement

The measurement uncertainty refers to CISPR 16-4-2:2003. The coverage factor $k = 2$ yields approximately a 95 % level of confidence.

<Conduction 01>

AMN: $\pm 3.29\text{dB}$

ISN: $\pm 4.43\text{dB}$

<OATS 01 (10M)>

Horizontal

30MHz~200MHz: $\pm 3.06\text{dB}$

200MHz~1000MHz: $\pm 3.22\text{dB}$

Vertical

30MHz~200MHz: $\pm 3.41\text{dB}$

200MHz~1000MHz: $\pm 3.20\text{dB}$

<Chamber 01 (3M)>

1GHz~6GHz: $\pm 4.69\text{dB}$

6GHz~18GHz: $\pm 4.72\text{dB}$

18GHz~26.5GHz: $\pm 3.44\text{dB}$

18GHz~26.5GHz: $\pm 3.49\text{dB}$

<Immunity 01>

Test item	Uncertainty	Test item	Uncertainty
EN61000-4-2 (ESD)		EN61000-4-5 (Surge)	
Rise time t_r	$\leq 15\%$	Time	$\pm 1.16\%$
Peak current I_p	$\leq 6.3\%$	Voltage	$\pm 1.63\%$
current at 30 ns	$\leq 6.3\%$	Current	$\pm 1.28\%$
current at 60 ns	$\leq 6.3\%$	EN61000-4-6 (CS)	
EN61000-4-3 (RS)	$\pm 2.19\text{dB}$	CDN	$\pm 1.36\text{dB}$
EN61000-4-4 (EFT)		EM Clamp	$\pm 3.19\text{dB}$
Time	$\pm 1.43\%$	EN61000-4-8 (Magnetic)	$\pm 1.12\%$
Voltage	$\pm 1.11\%$	EN61000-4-11 (Dips)	
Current	$\pm 1.85\%$	Time	$\pm 1.16\%$
		Voltage	$\pm 0.10\%$

Test item	Uncertainty	Test item	Uncertainty
EN61000-3-2 (Harmonics)	$\pm 4.43\%$	EN61000-3-3 (Fluctuations and Flicker)	$\pm 4.43\%$

14.3 Appendix C: Photographs of EUT

Please refer to the File of **ISL-13HE041P**